

notification to the NSO applicant of receipt of the other smelter's letter of intent, unless the issuing agency determines that the DLAs do not overlap. Failure of the NSO applicant to submit such a plan shall constitute grounds for denial of its NSO application or a violation of an effective NSO, as applicable.

(e) *The SCS operational manual.* Each NSO shall require the smelter to be operated in accordance with the provisions of an SCS operational manual approved by the issuing agency. The SCS operational manual shall describe the circumstances under which, the extent to which, and the procedures through which emissions shall be curtailed to prevent violations of the NAAQS in the smelter's DLA. Failure to curtail emissions when and as much as indicated by the manual or to follow the provisions of the manual implementing the requirements of paragraph (e)(3) of this section shall constitute a violation of the NSO.

(1) The operational manual shall prescribe emission curtailment decisions based on the use of real time information from the air quality monitoring network dispersion model estimates of the effect of emissions on air quality, and meteorological observations and predictions.

(2) The operational manual shall also provide for emission curtailment to prevent violation of the NAAQS within the smelter's DLA which may be caused in part by stack emissions, and to the extent practicable fugitive emissions, from any other source (unless that other source is a smelter subject to an NSO).

(3) The SCS operational manual shall include (but not be limited to):

(i) A clear delineation of the authority of the SCS operator to require all other smelter personnel to implement the operator's curtailment decisions;

(ii) The maintenance and calibration procedures and schedules for all SCS equipment;

(iii) A description of the procedures to be followed for the regular acquisition of all meteorological information necessary to operate the system;

(iv) The ambient concentrations and meteorological conditions that will be used as criteria for determining the

need for various degrees of emission curtailment;

(v) The meteorological variables as to which judgments may be made in applying the criteria stated pursuant to paragraph (e)(3)(iv) of this section;

(vi) The procedures through which and the maximum time period within which a curtailment decision will be made and implemented by the SCS operator;

(vii) The method for immediately evaluating the adequacy of a particular curtailment decision, including the factors to be considered in that evaluation;

(viii) The procedures through which and the time within which additional necessary curtailment will immediately be effected; and

(ix) The procedures to be followed to protect the NAAQS in the event of a mechanical failure in any element of the SCS.

(f) *Continuing review and improvement of the SCS.* Each NSO shall require the smelter owner to conduct an active program to continuously review the design and operation of the SCS to determine what measures may be available for improving the performance of the system. Among the elements of this program shall be measures to locate and examine possible places both inside and outside the DLA where unmonitored NAAQS violations may be occurring. Such measures shall include the use of modeling as appropriate and mobile ambient air quality monitors, following up on information and complaints from members of the public, and other appropriate activities. The NSO shall also require the submission of a semi-annual report to the issuing agency detailing the results of this review and specifying measures implemented to prevent the recurrence of any violations of NAAQS.

#### § 57.403 Written consent.

(a) *The consent.* The NSO shall include a written consent, signed by a corporate official empowered to do so, in the following form:

As a condition of receiving a Primary Non-ferrous Smelter Order (NSO) under Section 119 of the Clean Air Act, for the smelter operated by (name of company) at (location),

## Environmental Protection Agency

## § 57.404

the undersigned official, being empowered to do so, consents for the company as follows:

(1) In any civil proceeding (judicial or administrative) to enforce the NSO, the company will not contest:

(a) Liability for any violation of the National Ambient Air Quality Standards for sulfur dioxide in the smelter's designated liability area (DLA), except on the ground that a determination under 40 CFR 57.402(c)(3) was clearly wrong; or

(b) The conclusive allocation of liability under NSO provisions satisfying 40 CFR 57.402(d)(1) between the company's smelter and any other smelter(s) for any violation of the National Ambient Air Quality Standards for sulfur dioxide in an area of overlapping DLAs.

(2) The issuing agency (as defined in 40 CFR 57.103) will be allowed unrestricted access at reasonable times to inspect, verify calibration of, and obtain data from ambient air quality monitors operated by the company under the requirements of the NSO.

(b) *Rights not waived by the consent.* This consent shall not be deemed to waive any right(s) to judicial review of any provisions of an NSO that are otherwise available to the smelter owner or operator under section 307(b) of the Clean Air Act.

### § 57.404 Measurements, records, and reports.

(a) *Measurements.* Each NSO shall require the smelter owner to install, operate, and maintain a measurement system(s) for continuously monitoring sulfur dioxide emissions and stack gas volumetric flow rates in each stack (except a stack used exclusively for bypassing control equipment) which could emit 5 percent or more of the smelter's total potential (uncontrolled) hourly sulfur dioxide emissions.

(1) Such monitors shall be installed, operated, and maintained in accordance with the performance specifications and other requirements contained in appendices D and E to 40 CFR part 52. The monitors must take and record at least one measurement of sulfur dioxide concentration and stack gas flow rate from the effluent of each affected stack in each fifteen-minute period. (The NSO shall require the smelter operator to devise and implement any procedures necessary for compliance with these performance specifications.)

(2) The sampling point shall be located at least eight stack diameters

(diameter measured at sampling point) downstream and two diameters upstream from any flow disturbance such as a bend, expansion, constriction, or flame, unless another location is approved by the Administrator.

(3) The sampling point for monitoring emissions shall be in the duct at the centroid of the cross section if the cross sectional area is less than 4.645 m<sup>2</sup> (50 ft<sup>2</sup>) or at a point no closer to the wall than 0.914m (3 ft) if the cross sectional area is 4.645 m<sup>2</sup> (50 ft<sup>2</sup>) or more. The monitor sample point shall be in an area of small spatial concentration gradient and shall provide a sample which is representative of the concentration in the duct.

(4) The measurement system(s) installed and used pursuant to this paragraph shall be subject to the manufacturer's recommended zero adjustment and calibration procedures at least once per 24-hour operating period unless the manufacturer specifies or recommends calibration at shorter intervals, in which case such specifications or recommendations shall be followed. Records of these procedures shall be made which clearly show instrument readings before and after zero adjustment and calibration.

(5) The results of such monitoring, calibration, and maintenance shall be submitted in the form and with the frequency specified in the NSO.

(b) *Records.* Each NSO shall require the smelter owner to maintain records of the air quality measurements made, meteorological information acquired, emission curtailment ordered (including the identity of the persons making such decisions), and calibration and maintenance performed on SCS monitors during the operation of the SCS. These records shall be maintained for the duration of the NSO.

(c) *Reports.* Each NSO shall require the smelter owner to:

(1) Submit a monthly summary indicating all places and times at which the NAAQS for SO<sub>2</sub> were violated in the smelter's DLA, and stating the SO<sub>2</sub> concentrations at such times;

(2) Immediately notify EPA and the State agency any time concentrations of SO<sub>2</sub> in the ambient air in the smelter's DLA reaches 0.3 part per million (800 micrograms/cubic meter), 24-hour